

Combustible Gas Detector Portable Gas Leak Tester with Sound-light Alarm



Description:

Portable compound gas alarming detector can be checked four kinds of poisonous and harmful gas at the same time which has small size, safety save electricity, all English and simple operation.

Display:

dot matrix liquid crystal display in English With real-time storage capabilities, can realize real time record on alarm and time With PC interface, can be connected to computer (CO, H₂S, NO, NO₂, SO₂, CL₂, NH₃, O₃, H₂, O₂, EX) can be combine by random. 4-in-1 standard configuration is (O₂+EX+CO+H₂S)

Features:

Battery power supply (1500mAh)

Display: dot matrix liquid crystal display in English

With real-time storage capabilities, can realize real time record on alarm and time

With PC interface, can be connected to computer

(CO, H₂S, NO, NO₂, SO₂, CL₂, NH₃, O₃, H₂, O₂, EX) can be combine by random. 4-in-1 standard configuration is (O₂+EX+CO+H₂S)

Specification:

Size: 108mm * 61mm * 40mm

Weight: 151g

Sensor types: electrochemical method (gas catalytic combustion type, special separately)

Detection of gases: oxygen (O₂), gas (EX), poisonous and harmful gases (CO, H₂S)

Response time: ≤30s(O₂), ≤40s(CO), ≤20s(EX), ≤30s (H₂S)

Time display: the machine is year, month, day, and the clock display function

Display: dot matrix liquid crystal display in English High brightness

white backlight

Alarm: voice alarm more than 90dB (10cm away from instrument)

Light alarm red LED

Work mode: continuous work

Temperature range: - 20°C - 50°C

Humidity: 15% - 95% RH (no condensation)

Power supply: the lithium battery power supply (1500mAh)

Charging time: 3 - 5 hours

Charging voltage: DC5V

Package weight: 350g

Package included:

- 1. Portable compound gas alarming detector*
- 2. User Manual*